

OM-32 QC

The OM-32 is an electrically operated workshop crimping machine designed to up to crimp up to 2" 4 wire. Perfect for batch size hose assemblies it is quick, reliable and easy to use. Available in 1 phase and 3 phase (special voltages on request) and comes with an 12 off die set as standard.

The OM-32 QC features a floor mounted quick change rack and tool for die storage and easy changing of die sets.



- **Hose capacity 3/16" to 2" 4 wire**
- **Dial adjusted digital position indicator**
- **Available in 1phz or 3phz**
- **Twin return strut design**
- **Quick change system**
- **12 off die set as standard**

TECHNICAL DATA

Hose capacity:	3/16" - 2" (4 wire)
Swaging ranges:	8mm - 82mm
Voltages:	220/240 single phase 50/60hz - 380/440 three phase 50/60hz
Radial swaging force:	2517 kN
Max opening without dies:	124mm
Max cycle time:	5 seconds closing 5 seconds opening
Pump:	Twin speed 4600 psi
Weight:	230 kg

OM-32 QC

The OM-32 is an electrically operated workshop crimping machine designed to up to crimp up to 2" 4 wire. Perfect for batch size hose assemblies it is quick, reliable and easy to use. Available in 1 phase and 3 phase (special voltages on request) and comes with an 12 off die set as standard.

The OM-32 QC features a floor mounted quick change rack and tool for die storage and easy changing of die sets.



DIE SET TABLE

Die Set	Range (mm)	Length (mm)	Max Ferrule Diameter (mm)	Die Set	Range (mm)	Length (mm)	Max Ferrule Diameter (mm)
08-32*	08.0 – 09.9	40.0	20.0	34-32	34.0 – 39.9	70.0	46.0
10-32*	10.0 – 11.9	40.0	22.0	40-32	40.0 – 45.9	70.0	52.0
12-32*	12.0 – 13.9	40.0	24.0	46-32	46.0 – 51.9	80.0	58.0
14-32*	14.0 – 15.9	40.0	26.0	52-32	52 – 57.9	80.0	64.0
16-32	16.0 – 18.9	40.0	28.0	58-32	58 – 63.9	80.0	70.0
19-32	19.0 – 21.9	40.0	31.0	64-32	64 – 69.9	80.0	66.0
22-32	22.0 – 25.9	50.0	34.0	70-32	70 – 82.0	95.0	82.0
26-32	26.0 – 27.9	50.0	38.0				
28-32*	28.0 – 29.9	50.0	40.0				
30-32	30.0 – 33.9	60.0	42.0				

*Non standard dies